

HARBACH ELECTRONICS/PETER W. DAHL AMATEUR TRANSFORMER DATABASE

3

3000 VAC @ 1.0A CCS N PLATE TRANSFORMER
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 3000 VAC @ 1.0A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3000 VAC @ 1.5A CCS HI/LO PRI LO TAP TO PROVIDE 2000 VAC
CORE) A-518 STYLE #) 10 HIPERSIL C-CORE
PR) 220 VAC 60 HZ 1 PH WITH HI/LO TAPS
S1) 3000/2000 VAC @ 1.5 AMP CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3000 VAC @ 2A CCS WITH 2650 VAC TAP & 220-230-240-250V PRI
CORE) A-0525/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-230-240-250 VAC 60 HZ 1 PH
S1) 0-2650-3000 VAC @ 2A CCS OR 3A ICAS
DM) HT = 9.769 WT = 9.825 DT = 9.188 MD = 5.000 MW = 6.437 WEIGHT) 86 LBS

3000 VAC @ 3A CCS N PLATE TRANSFORMER
CORE) A-0530/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 220/240 VAC 60 HZ 1 PH
S1) 3000 VAC @ 3.0A CCS
DM) HT = 11.375 WT = 10.700 DT = 9.813 MD = 5.625 MW = 6.500 WEIGHT) 127 LBS

3000/1800 VAC @ 1.0A CCS N PLATE TRANSFORMER WITH HI/LO SEC TAPS
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 0-1800-3000 VAC @ 1.0A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3000/2000 VCT @ 0.35A CCS SPECIAL FOR C&N SERVICES
CORE) A-393 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 120 VAC 60 HZ 1 PH
S1) 1500-1000-0-1000-1500 VAC @ 0.35A CCS
DM) HT = 6.000 WT = 6.325 DT = 6.281 MD = 3.625 MW = 4.000 WEIGHT) 23 LBS

3000/2000 VCT @ 0.5A CCS SPECIAL FOR C&N SERVICES
CORE) A-274 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 120 VAC 60 HZ 1 PH
S1) 1500-1000-0-1000-1500 VAC @ 0.5A CCS
DM) HT = 7.125 WT = 7.825 DT = 7.063 MD = 3.625 MW = 4.875 WEIGHT) 37 LBS

3000/2400 VAC @ 1.5A CCS JKL PLATE TRANSFORMER
CORE) A-518 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-230-240 VAC 60 HZ 1 PH
S1) 0-2400-3000 VAC @ 1.5A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3000/2500/2000 VAC @ 1A CCS PLATE TRANSFORMER
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 0-2000-2500-3000 VAC @ 1.0 AMP CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3000/2800/2600V @ 1.5A CS JL PLATE TRANSFORMER
CORE) A-518 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 0-2600-2800-3000 VAC @ 1.5A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

32/28/24 VAC @ 15A CCS PROP PITCH PWR XFMR WITH 220 VAC 50/60HZ
CORE) EI-162 X 2.5" 29GA M6X STYLE #) 02 E-I LAMINATED CORE
PR) 220 VAC 50/60 HZ 1 PH
S1) 0-24-28-32 VAC @ 15A CCS
DM) HT = 4.250 WT = 5.750 DT = 5.650 MD = 3.625 MW = 4.937 WEIGHT) 18 LBS

3200 VAC @ 1.0A CCS SP PLATE XFMR FOR 4000 VDC @ 0.8A FWB CAP-I
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-100-110-120 VAC 60 HZ 1 PH
S1) 3200 VAC @ 1.0A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3200 VAC @ 1.5A CCS JK PLATE TRANSFORMER
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-230 VAC 60 HZ 1 PH
S1) 3200 VAC @ 1.5A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3200 VCT @ .4A & 5 VCT @ 15A PLATE & FIL XFMR FOR SINGLE 3-500Z
CORE) EI-162 X 3 STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 3200 VCT @ 0.4A ICAS
S2) 5.0 VCT @ 15A CCS
DM) HT = 5.750 WT = 4.250 DT = 6.150 MD = 4.125 MW = 3.437 WEIGHT) 21 LBS

3200/2800/2400 VAC @ 1.3A CS CCS PLATE XFMR WITH SCREW LUGS ON COIL
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 0-2400-2800-3200 VAC @ 1.3A CCS
DM) HT = 9.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3300/2300 VAC @ 2.0A CCS KL PLATE TRANSFORMER
CORE) A-0525/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-230-240 VAC 60 HZ 1 PH
S1) 0-2300-3300 VAC @ 2.0A CCS
DM) HT = 10.769 WT = 9.825 DT = 9.188 MD = 5.000 MW = 6.437 WEIGHT) 86 LBS

3500 VAC @ 1.0A CCS PLATE TRANSFORMER
CORE) A-518 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 220 VAC 60 HZ 1PH
S1) 3500 VAC @ 1.0A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3500 VAC @ 1.0A ICAS G ADVERTISED UNIT
CORE) A-0480/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 3500 VAC @ 1.0A ICAS
DM) HT = 8.375 WT = 8.075 DT = 7.688 MD = 3.937 MW = 5.500 WEIGHT) 46 LBS

3500 VAC @ 1.5A JK PLATE TRANSFORMER
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-230 VAC 60 HZ 1 PH
S1) 3500 VAC @ 1.5A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3500 VAC @ 2.0A CCS N PLATE TRANSFORMER
CORE) A-0555/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 3500 VAC @ 2.0A CCS
DM) HT = 12.856 WT = 12.765 DT = 9.100 MD = 4.375 MW = 8.510 WEIGHT) 119 LBS

3500 VAC @ 4.0A CCS N PLATE TRANSFORMER
CORE) A-550 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 3500 VAC @ 4.0A CCS
DM) HT = 15.438 WT = 15.950 DT = 10.750 MD = 6.750 MW = 10.000 WEIGHT) 253 LBS

3500/2000 VAC @ 1.5A CCS JK PLATE TRANSFORMER
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-230 VAC 60 HZ 1 PH
S1) 0-2000-3500 VAC @ 1.5A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3500/2400 VAC @ 2.0A CCS L PLATE TRANSFORMER
CORE) A-0555/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 240 VAC 60 HZ 1 PH
S1) 0-2400-3500 VAC @ 2.0A CCS
DM) HT = 12.856 WT = 12.765 DT = 9.100 MD = 4.375 MW = 8.510 WEIGHT) 119 LBS

3500/3200/3000 VAC @ 1A ICAS PLATE TRANSFORMER
CORE) A-480 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-230-240 VAC 60 HZ 1 PH
S1) 0-3000-3200-3500 VAC @ 1.0A ICAS
DM) HT = 8.375 WT = 8.075 DT = 7.688 MD = 3.937 MW = 5.500 WEIGHT) 46 LBS

3600 VAC @ 1.0 AMP CCS G WITH TAPS AT 1900-2000-2600 VAC
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 0-1900-2000-2600-3600 VAC @ 1.0 AMP CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3600 VAC @ 1.5A ICAS N PLATE TRANSFORMER
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 3600 VAC @ 1.5A ICAS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3600 VAC @ 2.0A ICAS J PLATE TRANSFORMER
CORE) A-0525/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 220 VAC 60 HZ 1 PH
S1) 3600 VAC @ 2.0A ICAS
DM) HT = 10.769 WT = 9.825 DT = 9.188 MD = 5.000 MW = 6.437 WEIGHT) 86 LBS

3750 VAC @ 1.0A CCS G PLATE TRANSFORMER
CORE) A-518 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 3750 VAC @ 1.0A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

3800 VAC @ 4.0A CCS L PLATE TRANSFORMER
CORE) A-0550/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 240 VAC 60 HZ 1 PH
S1) 3800 VAC @ 4.0A CCS
DM) HT = 15.688 WT = 15.950 DT = 10.750 MD = 6.750 MW = 10.000 WEIGHT) 253 LBS

3800/3000 VAC @ 3.0A CCS PLATE TRANSFORMER
CORE) A-0540/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 0-3000-3800 VAC @ 3.0A CCS
DM) HT = 13.500 WT = 11.950 DT = 10.125 MD = 5.625 MW = 7.500 WEIGHT) 164 LBS

3800/3500/2800V @ 1.0A CCS N PLATE TRANSFORMER
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 0-2800-3500-3800 VAC @ 1.0A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS