

HARBACH ELECTRONICS/PETER W. DAHL AMATEUR TRANSFORMER DATABASE

7

7.0 VCT @ 160A CCS I DUAL 3CX6000A7/YU-148 FILAMENT XFMR
CORE) A-0274/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 7.0 VCT @ 160A CCS
DM) HT = 7.125 WT = 7.825 DT = 7.063 MD = 3.625 MW = 4.875 WEIGHT) 37 LBS

7.0 VCT @ 85A N YU-148 FILAMENT TRANSFORMER
CORE) EI-162 X 3 STYLE #) 02 E-I LAMINATED CORE
PR) 0-220-240 VAC 60 HZ 1 PH
S1) 7.0 VCT @ 85A CCS
DM) HT = 4.250 WT = 5.750 DT = 6.150 MD = 4.125 MW = 4.937 WEIGHT) 21 LBS

7.5 VCT @ 100A G FILAMENT TRANSFORMER
CORE) EI-162 X 3.5 STYLE #) 02 E-I LAMINATED CORE
PR) 115/230 VAC 50/60 HZ 1 PH
S1) 7.5 VCT @ 100A CCS
DM) HT = 5.000 WT = 5.750 DT = 6.650 MD = 4.625 MW = 4.937 WEIGHT) 24 LBS

7.5 VCT @ 21A ABD 4-1000A OR 3-1000Z FILAMENT TRANSFORMER
CORE) EI-150 X 2 STYLE #) 05 E-I LAMINATED CORE
PR) 0-110-115-120 VAC 60 HZ 1 PH
S1) 7.5 VCT @ 21A CCS
DM) HT = 4.500 WT = 3.750 DT = 4.375 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

7.5 VCT @ 21A E 4-1000A OR 3-1000Z FILAMENT TRANSFORMER
CORE) EI-150 X 2 STYLE #) 05 E-I LAMINATED CORE
PR) 0-105-117 VAC 60 HZ 1 PH
S1) 7.5 VCT @ 21A CCS
DM) HT = 4.500 WT = 3.750 DT = 4.375 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

7.5 VCT @ 21A LO PROFILE FILAMENT TRANSFORMER
CORE) EI-125 X 2" 29G M6X STYLE #) 04 E-I LAMINATED CORE
PR) 0-105-117 VAC 60 HZ 1 PH
S1) 7.5 VCT @ 21A CCS
DM) HT = 3.750 WT = 3.125 DT = 3.575 MD = 3.000 MW = 2.500 WEIGHT) 7 LBS

7.5 VCT @ 42A CCS LP SP LO PROFILE SPECIAL PRIMARY FOR T. GAISER
CORE) EI-150 X 2.5" 29GAM6 STYLE #) 02 E-I LAMINATED CORE
PR) 0-115-125 VAC 60 HZ 1 PH
S1) 7.5 VCT @ 42A CCS
DM) HT = 3.750 WT = 4.500 DT = 4.390 MD = 3.500 MW = 3.750 WEIGHT) 12 LBS

7.5 VCT @ 55A G ADERVTISED UNIT
CORE) EI-162 X 2 STYLE #) 02 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 7.5 VCT @ 55A CCS
DM) HT = 4.250 WT = 5.750 DT = 5.150 MD = 3.125 MW = 4.937 WEIGHT) 15 LBS

7.5 VCT @ 75A G ADVERTISED UNIT

CORE) EI-162 X 3 STYLE #) 02 E-I LAMINATED CORE

PR) 115/230 VAC 60 HZ 1 PH

S1) 7.5 VCT @ 75A CCS

DM) HT = 4.250 WT = 5.750 DT = 6.150 MD = 4.125 MW = 4.937 WEIGHT) 21 LBS

7000 VAC @ 2.5A CCS PLATE TRANSFORMER (AMATEUR SERVICE)

CORE) A-550 C-CORE STYLE #) 10 HIPERSIL C-CORE

PR) 220 VAC 60 HZ 1 PH

S1) 7000 VAC @ 2.5A CCS

DM) HT = 15.438 WT = 15.950 DT = 10.750 MD = 6.750 MW = 10.000 WEIGHT) 253 LBS

7000 VAC @ 6A ICAS PLATE TRANSFORMER

CORE) A-1179/ C-CORE STYLE #) 10 HIPERSIL C-CORE

PR) 220 VAC 60 HZ 1 PH

S1) 7000 VAC @ 6A ICAS

DM) HT = 19.125 WT = 18.200 DT = 13.000 MD = 8.250 MW = 12.500 WEIGHT) 441 LBS

7200 VCT @ 2.1 AMP CCS FOR FWCT TO DELIVER 4400 VDC @ 1.5A CCS

CORE) A-555 C-CORE STYLE #) 10 HIPERSIL C-CORE

PR) 0-220 VAC 60 HZ 1 PH

S1) 0-3600-7200 VCT @ 2.1A CCS

DM) HT = 12.856 WT = 12.765 DT = 9.100 MD = 4.375 MW = 8.510 WEIGHT) 119 LBS