

HARBACH ELECTRONICS/PETER W. DAHL AMATEUR TRANSFORMER DATABASE

B

B&W PT-2500A PLATE XFMR (ER) REWIND USING OLD MOUNTING HARDWARE
CORE) EI-200 X 4.5" 29GA M6 STYLE #) 04 E-I LAMINATED CORE
PR) 0-120-148 & 0-120-148 VAC 60 HZ 1 PH
S1) 1375 VAC @ 0.8A CCS
DM) HT = 6.000 WT = 5.000 DT = 7.020 MD = 6.125 MW = 3.500 WEIGHT) 40 LBS

B&W PT2500A FIL & IND POWER FOR CONVERSION TO SINGLE 3CX1200A7
CORE) EI-150 X 2 STYLE #) 04 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 115 VAC @ 0.1A CCS
S2) 6.0 VAC @ 1.0A CCS
S3) 7.5 VCT @ 21A CCS
DM) HT = 5.000 WT = 3.750 DT = 3.890 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

B&W PT2500A7 OUTBOARD PLATE FOR SINGLE 3CX1200A7 CONVERSION
CORE) A-518 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH WITH HI/LO TAPS
S1) 1485/1143 VAC @ 2.75A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

BTI LK-2000 PLATE FOR BRAD THOMPSON INDUSTRIES LK-2000
CORE) A-0480/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 1250 VAC @ 1.5A CCS
DM) HT = 8.375 WT = 8.075 DT = 7.688 MD = 3.937 MW = 5.500 WEIGHT) 46 LBS

BTI LK-2000 PLATE/FILAMENT COMBINATION PLATE & FILAMENT TRANSFORMER
CORE) A-0480/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 1250 VAC @ 1.5A CCS
S2) 7.5 VCT @ 21A CCS
DM) HT = 8.375 WT = 8.075 DT = 7.688 MD = 3.937 MW = 5.500 WEIGHT) 46 LBS