

HARBACH ELECTRONICS/PETER W. DAHL AMATEUR TRANSFORMER DATABASE

G

GALAXY V POWER TRANSFORMER

CORE) EI-175 X 2 STYLE #) 02 E-I LAMINATED CORE

PR) 117 VAC 60 HZ 1 PH

S1) 860 VAC @ 250MA CCS

S2) 285 VAC @ 175MA CCS

S3) 80 VAC @ 50MA CCS

S4) 24 VCT @ 500MA CCS

S5) 12.6 VAC @ 6A CCS

DM) HT = 4.375 WT = 5.250 DT = 4.205 MD = 3.125 MW = 4.375 WEIGHT) 14 LBS

GLOBE CHAMPION LV POWER T1 LV, BIAS, FIL VOLTS FOR MODELS 300 & 350

CORE) EI-150 X 2.5" 29GA M6 STYLE #) 05 E-I LAMINATED CORE

PR) 115 VAC 60 HZ 1 PH

S1) 900 VCT @ 250MA CCS

S2) 110 VAC @ 0.1A CCS

S3) 12.6 VCT @ 3A CCS

S4) 5 VAC @ 3A CCS

S5) 6.3 VCT @ 6A CCS & 6.3 VAC @ 6A CCS

S6) 2.5 VCT @ 10A CCS

DM) HT = 4.500 WT = 3.750 DT = 4.875 MD = 3.500 MW = 3.000 WEIGHT) 12 LBS

GLOBE CHAMPION 175 POWER T3 THORDARSON P/N T-21P93

CORE) EI-150 X 2.5" 29GA M6X STYLE #) 05 E-I LAMINATED CORE

PR) 117 VAC 60 HZ 1 PH

S1) 2150/1000 VCT @ 95/125 MA CCS FWCT

DM) HT = 4.500 WT = 3.750 DT = 4.875 MD = 3.500 MW = 3.000 WEIGHT) 12 LBS

GLOBE CHAMPION 300 MOD XFMR PP 809 MODULATORS TO PARALLEL 9909 RF PA

CORE) EI-162 X 1.625 STYLE #) 04 E-I LAMINATED CORE

PR) 11,000 OHMS P-P (PP 809'S) (1280 VCT)

S1) 2830 OHMS (920 VDC @ 325 MA, 650 VRMS)

DM) HT = 5.750 WT = 4.250 DT = 4.775 MD = 2.750 MW = 3.437 WEIGHT) 13 LBS

GLOBE KING 500A LV POWER THORDARSON T-21P89

CORE) EI-125 X 2 STYLE #) 05 E-I LAMINATED CORE

PR) 115 VAC 60 HZ 1 PH

S1) 1160 VCT @ 150MA CCS

DM) HT = 3.750 WT = 3.125 DT = 4.125 MD = 3.000 MW = 2.500 WEIGHT) 7 LBS

GLOBE KING 500A MOD POWER 1000 VDC FOR 811A'S & 400 VDC FOR 6L6G

CORE) EI-162 X 2 STYLE #) 02 E-I LAMINATED CORE

PR) 117 VAC 60 HZ 1 PH

S1) 1160-350-0-350-1160 VAC @ 450MA ICAS

DM) HT = 4.250 WT = 5.750 DT = 5.150 MD = 3.125 MW = 4.937 WEIGHT) 15 LBS

GLOBE KING 500A MOD XFMR PP 811A'S TO SINGLE 4-250A/4-400A RF PA

CORE) EI-150 X 3.5" 29GA M6X STYLE #) 05 E-I LAMINATED CORE

PR) 1465 VCT @ 0.246A CCS (7400 OHMS P-P)

S1) 1275 VAC @ 0.283A CCS (1800 VDC @ .4A)

DM) HT = 4.500 WT = 3.750 DT = 5.390 MD = 4.500 MW = 3.000 WEIGHT) 16 LBS

GLOBE KING 500B PLATE 1800 VDC @ 400 MA CCS FWB CHOKE INPUT
CORE) EI-175 X 5 STYLE #) 05 E-I LAMINATED CORE
PR) 115 VAC 60 HZ 1 PH
S1) 4000 VCT @ 400MA ICAS (FWCT)
DM) HT = 5.250 WT = 4.375 DT = 8.000 MD = 6.125 MW = 3.500 WEIGHT) 31 LBS

GLOBE KING 500C SCREEN CHOKE CH1 SCREEN SUPPLY DC FILTER CHOKE
CORE) EI-075 X .75 STYLE #) 01 E-I LAMINATED CORE
PR) 25 HY @ 0.050A DC (400 WVDC)
DM) HT = 1.955 WT = 2.330 DT = 1.575 MD = 0.000 MW = 2.813 WEIGHT) 1 LBS

GLOBE SCOUT 65A POWER XFMR WRL MODEL 65A GLOBE SCOUT TRANSMITTER
CORE) EI-150 X 2" 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 115 VAC 60 HZ 1 PH
S1) 1200 VCT @ 0.2A CCS (500 VDC FWCT)
S2) 6.3 VAC @ 3.5A CCS
S3) 5 VAC @ 3A CCS
DM) HT = 4.500 WT = 3.750 DT = 3.890 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

GONSET G-76 POWER XFMR T-1, MAIN POWER TRANSFORMER
CORE) EI-175 X 2.5" 29GA M6X STYLE #) 06 E-I LAMINATED CORE
PR) 115 VAC 60 HZ 1 PH
S1) 1300/540 VCT @ 0.3A CCS
S2) 5.0 VAC @ 4A CCS
S3) 12.6 VAC @ 5A CCS
DM) HT = 3.750 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 17 LBS

GONSET GSB-100 POWER ADVERTISED UNIT
CORE) EI-150 X 2 STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 720-260-0-130-260-720 VAC @ 150MA CCS
S2) 5.0 VAC @ 3A CCS
S3) 5.0 VAC @ 3A CCS
S4) 6.3 VAC @ 10A CCS
DM) HT = 4.500 WT = 3.750 DT = 3.890 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

GONSET GSB-101 ALT PLATE C ALT XFMR ON EI-175 LAMS WITH 117 VAC PRI
CORE) EI-175 X 5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 3600 VCT @ 500MA CCS
DM) HT = 5.250 WT = 4.375 DT = 7.205 MD = 6.125 MW = 3.500 WEIGHT) 31 LBS

GONSET GSB-101 ALT PLATE J ALT XFMR ON EI-175 LAMS WITH 220 VAC PRI
CORE) EI-175 X 5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 220 VAC 60 HZ 1 PH
S1) 3600 VCT @ 500MA CCS
DM) HT = 5.250 WT = 4.375 DT = 7.205 MD = 6.125 MW = 3.500 WEIGHT) 31 LBS

GONSET GSB-101 ER PLATE C EXACT REPLACEMENT UNIT WITH 117 VAC PRI
CORE) EI-162 X 3.5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 3600 VCT @ 500MA CCS
DM) HT = 5.750 WT = 4.250 DT = 6.650 MD = 4.625 MW = 3.437 WEIGHT) 24 LBS

GONSET GSB-101 ER PLATE J EXACT REPLACEMENT UNIT WITH 220 VAC PRI
CORE) EI-162 X 3.5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 220 VAC 60 HZ 1 PH
S1) 3600 VCT @ 500MA CCS
DM) HT = 5.750 WT = 4.250 DT = 6.650 MD = 4.625 MW = 3.437 WEIGHT) 24 LBS

GONSET GSB-101 FILTER CHOKE EXACT REPLACEMENT

CORE) EI-150 X 2 STYLE #) 05 E-I LAMINATED CORE

PR) 25 HY @ 75 MA TO 5 HY @ 450MA DC

DM) HT = 4.500 WT = 3.750 DT = 4.375 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

GONSET GSB-101 PLATE HEAVY DUTY HIPERSIL REPLACEMENT XFMR

CORE) A-0203/ C-CORE STYLE #) 10 HIPERSIL C-CORE

PR) 117 VAC 60 HZ 1 PH

S1) 3600 VCT @ 600MA CCS

DM) HT = 6.375 WT = 7.950 DT = 6.813 MD = 3.375 MW = 5.000 WEIGHT) 30 LBS

GONSET GSB-201 MK IV POWER TRANSFORMER

CORE) EI-175 X 5 29GA MX6 STYLE #) 04 E-I LAMINATED CORE

PR) 120/240 VAC 60 HZ 1 PH

S1) 2500 VAC @ 1.0A ICAS (0.3A CCS)

S2) 6.3 VAC @ 16A CCS

DM) HT = 5.250 WT = 4.375 DT = 7.205 MD = 6.125 MW = 3.500 WEIGHT) 31 LBS

GONSET GSB-201 POWER ADVERTISED UNIT

CORE) EI-175 X 5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE

PR) 120/240 VAC 60 HZ 1 PH

S1) 1705 VAC @ 500MA CCS

S2) 6.3 VAC @ 20A CCS

DM) HT = 5.250 WT = 4.375 DT = 7.205 MD = 6.125 MW = 3.500 WEIGHT) 31 LBS

GONSET GSB-201-1 POWER SPECIAL WITH 12.6 V FIL & 540 VCT WNDGS

CORE) EI-175 X 5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE

PR) 120/240 VAC 60 HZ 1 PH

S1) 1705 VAC @ 500MA CCS

S2) 12.6 VAC @ 8A CCS

S3) 540 VCT @ 0.1A CCS

DM) HT = 5.250 WT = 4.375 DT = 7.205 MD = 6.125 MW = 3.500 WEIGHT) 31 LBS