

HARBACH ELECTRONICS/PETER W. DAHL AMATEUR TRANSFORMER DATABASE

Y

YAESU FL-2000B LV PWR T2 FILAMENT & CONTROL VOLTAGE TRANSFORMER
CORE) EI-112 X 1.5" 29GA M6X STYLE #) 02 E-I LAMINATED CORE
PR) 0-100-110-117 & 0-100-110-117 VAC 60 HZ 1 PH
S1) 6.5 VCT @ 8A CCS
S2) 13 VAC @ 1A CCS
DM) HT = 2.813 WT = 3.375 DT = 2.918 MD = 2.500 MW = 2.812 WEIGHT) 4 LBS

YAESU FL-2100B POWER XFMR P/N 21002, T1, FOR PAIR OF 572B'S
CORE) EI-175 X 3.5 STYLE #) 06 E-I LAMINATED CORE
PR) 0-100-110-117 & 0-100-110-117 VAC 60 HZ 1 PH
S1) 0-425-620-850 VAC @ 1A ICAS
S2) 6.5 VCT @ 8A CCS
S3) 13 VAC @ 1A CCS
DM) HT = 4.750 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 22 LBS

YAESU FT-901 POWER XFMR WITHOUT DC WINDINGS & DUAL PRIMARY
CORE) EI-137 X 2.5 STYLE #) 06 E-I LAMINATED CORE
PR) 0-100-110-117 VAC 60 HZ 1 PH
S1) 320 VCT @ 0.5A CCS
S2) 0-120-190-250 VAC @ 0.1A CCS
S3) 11.5-0-11.5-12.6 VAC @ 2A CCS
DM) HT = 3.437 WT = 4.125 DT = 3.437 MD = 2.750 MW = 3.437 WEIGHT) 10 LBS

YAESU TEMPO AC ONE PWR XFMR TEMPO AC ONE POWER SUPPLY WITH SPEAKER
CORE) EI-150 X 2.5" 29GA M6X STYLE #) 06 E-I LAMINATED CORE
PR) 0-100-110-117 & 0-100-110-117 VAC 60 HZ 1 PH
S1) 0-240-460-600 VAC @ 0.275A CCS
S2) 270 VCT @ 0.2A CCS
S3) 100 VAC @ 0.1A CCS
S4) 6.3 VAC @ 6A & 6.3 VAC @ 6A
DM) HT = 3.688 WT = 4.500 DT = 3.750 MD = 3.000 MW = 3.750 WEIGHT) 12 LBS